



HLU Bearing No.	Type	Shaft Size in.	Dimensions (in./mm)							Load Ratings lbs		Weight lbs
			d		D		h	C	B	Dynamic Cr	Static Cor	
			Bore Nominal	+ 0 to minus Bore Tolerance	Outer Diameter	+ 0 to minus Outer Tolerance	Relube Hole Location	Outer Ring	Inner Ring			
GW209PPB2	1	1 3/4	1.7717 45.00	.0005 .013	3.3465 85	.0006 .015	.2480 6.30	1.1880 30.175	1.1880 30.175	8093	4602	1.22
GW209PPB4	1	1 1/2	1.535 39.00	.0100 .250	3.3465 85	.0006 .015	.2480 6.30	1.1880 30.175	1.1880 30.175	8093	4602	1.47
GW209PPB11	2	1 3/4	1.7811 45.24	.0100 .250	3.3465 85	.0006 .015	.2539 6.45	.8661 22	1.4380 36.525	8093	4602	1.28
ST209-1 1/2JD	5	1 1/2	1.5300 38.86	.0100 .250	3.3465 85	.0006 .015	.2594 6.59	1.1880 30.18	1.4380 36.53	8093	4602	1.80
ST209-1 3/4JD	5	1 3/4	1.7811 45.24	.0100 .250	3.3465 85	.0006 .015	.2594 6.59	1.1880 30.18	1.4380 36.53	8093	4602	1.55
GW210PPB2	1	1 15/16	1.9380 49.225	.0006 .015	3.5433 90	.0006 .015	.2390 6.07	1.1880 30.175	1.1880 30.175	8835	5215	1.36
GW210PPB5	1	1 3/4	1.7850 45.339	.0100 .250	3.5433 90	.0006 .015	.2390 6.07	1.1880 30.175	1.1880 30.175	8835	5215	1.65
GW211PP2	4	2 3/16	2.1880 55.575	.0006 .015	3.9370 100	.0006 .015	.2638 6.70	1.3120 33.325	1.3120 33.325	9756	6571	1.95
GW211PPB2	1	2 3/16	2.1880 55.575	.0006 .015	3.9370 100	.0006 .015	.2638 6.70	1.3120 33.325	1.3120 33.325	9756	6571	1.85
GW211PPB9	2	2 3/16	2.1950 55.75	.0070 .180	3.9370 100	.0006 .015	.2756 7.00	.9843 25	1.5620 39.69	9756	6571	1.86
GW211PPB13	2	1 3/4	1.7850 45.339	.0100 .254	3.9370 100	.0006 .015	.2756 7.00	.9843 25	1.3120 33.325	9756	6571	2.16
ST211-2 3/16JD	5	2 3/16	2.2047 56.00	.0100 .250	3.9370 100	.0006 .015	.3020 7.67	1.3120 33.34	1.5630 39.70	9756	6571	2.26
DC214TTR2A	3	2 3/4	2.7657 70.25	.0020 .050	4.9213 125	.0007 .018	.3669 9.32	1.5590 39.6	1.9960 50.7	13980	9891	4.20