



HLU Bearing No.	Bore Diameter d in.	Dimensions (in./mm)									Load Ratings lbs		Weight lbs
		D	B1	C	S	S1	B2	h	d1	ds	Dynamic Cr	Static Cor	
HL204-12	3/4	1.8504 47	1.2795 32.5	0.6299 16	0.5000 12.7	0.7795 19.8	0.3740 9.5	0.1575 4	1.7520 44.5	8-32X5/8 UNC	2886	1650	0.48
HL205-15 HL205-16	15/16 1	2.0472 52	1.4370 36.5	0.6693 17	0.5630 14.3	0.8740 22.2	0.4370 11.1	0.1654 4.2	1.9370 49.2	10-32x3/4 UNF	3150	1771	0.80
HL206-18 HL206-19 HL206-20	1 1/8 1 3/16 1 1/4	2.4409 62	1.5630 39.7	0.7480 19	0.6260 15.9	0.9370 23.8	0.4370 11.1	0.1969 5.0	2.1890 55.6	10-32x3/4 UNF	4375	2542	1.15
HL207-20 HL207-22 HL207-23	1 1/4 1 3/8 1 7/16	2.8346 72	1.7913 45.5	0.7874 20	0.6890 17.5	1.1024 28	0.5630 14.3	0.2244 5.7	2.6890 68.3	1/4-28x3/4 UNF	5770	3440	1.55
HL208-24	1 1/2	3.1496 80	2.0000 50.8	0.8268 21	0.7180 19	1.2520 31.8	0.5630 14.3	0.2362 6.0	2.7795 70.6	1/4-28x3/4 UNF	6636	4078	1.85
HL209-26 HL209-27 HL209-28	1 5/8 1 11/16 1 3/4	3.3464 85	2.0000 50.8	0.8661 22	0.7480 19	1.2520 31.8	0.5630 14.3	0.2480 6.3	3.0630 77.8	1/4-28x3/4 UNF	7120	4650	1.90
HL210-31 HL210-32	1 15/16 2	3.5433 90	2.0945 53.2	0.9449 24	0.7480 19	1.3465 34.2	0.5630 14.3	0.2598 6.6	3.3740 85.7	1/4-28x3/4 UNF	7884	5210	2.50
HL211-32 HL211-34 HL211-35	2 2 1/8 2 3/16	3.9370 100	2.2520 57.2	0.9843 25	0.8740 22.2	1.3740 34.9	0.6890 17.5	0.2756 7.0	3.6890 93.7	5/16-24x1 UNF	9752	6569	3.00
HL212-36 HL212-38 HL212-39	2 1/4 2 3/8 2 7/16	4.3307 110	2.6260 66.7	1.0630 27	1.0000 25.4	1.6260 41.3	0.6890 17.5	0.2992 7.6	4.1102 104.4	5/16-24x1 UNF	10736	7403	4.30

Refer to recommended cap screw tightening torque table for proper tightening torques.