


Standard B Type Seal



Optional Triple-lip seal
(+ Suffix - R3)

HLU Unit No.	Shaft Diameter in.	Dimensions (in./mm)									Bolt Used (in./mm)	Bearing No.	Housing No.	Weight lbs
		H	J	L	A ₂	A ₁	A	N	E	S				
HLFL204-12	3/4	4.4488 113	3.5433 90	2.3622 60	0.5906 15	0.4528 11.5	1.0039 25.5	0.3937 10	1.2795 32.5	0.5000 12.7	3/8 10	HL204-12	FL204	1.15
HLFL205-15 HLFL205-16	15/16 1	5.1181 130	3.8976 99	2.6772 68	0.6299 16	0.5118 13	1.0630 27	0.4528 11.5	1.4370 36.5	0.5630 14.3	7/16 11	HL205-15 HL205-16	FL205	1.72
HLFL206-18 HLFL206-19 HLFL206-20	1 1/8 1 3/16 1 1/4	5.8268 148	4.6063 117	3.1496 80	0.7087 18	0.5118 13	1.2205 31	0.4528 11.5	1.5630 39.7	0.6260 15.9	7/16 11	HL206-18 HL206-19 HL206-20	FL206	2.35
HLFL207-20 HLFL207-22 HLFL207-23	1 1/4 1 3/8 1 7/16	6.3386 161	5.1181 130	3.5433 90	0.7480 19	0.5906 15	1.3386 34	0.5118 13	1.7913 45.5	0.6890 17.5	1/2 12	HL207-20 HL207-22 HL207-23	FL207	3.05
HLFL208-24	1 1/2	6.8898 175	5.6693 144	3.9370 100	0.8268 21	0.5906 15	1.4173 36	0.5118 13	2.0000 50.8	0.7480 19	1/2 12	HL208-24	FL208	3.75
HLFL209-26 HLFL209-27 HLFL209-28	1 5/8 1 11/16 1 3/4	7.4016 188	5.8268 148	4.2520 108	0.8661 22	0.6299 16	1.4961 38	0.5906 15	2.0000 50.8	0.7480 19	9/16 14	HL209-26 HL209-27 HL209-28	FL209	4.30
HLFL210-31 HLFL210-32	1 15/16 2	7.7559 197	6.1811 157	4.5276 115	0.8661 22	0.6299 16	1.5748 40	0.5906 15	2.0945 53.2	0.7480 19	9/16 14	HL210-31 HL210-32	FL210	5.25
HLFL211-32 HLFL211-34 HLFL211-35	2 2 1/8 2 3/16	8.8189 224	7.2441 184	5.1181 130	0.9842 25	0.7087 18	1.6929 43	0.6496 16.5	2.2520 57.2	0.8740 22.2	5/8 16	HL211-32 HL211-34 HL211-35	FL211	6.20
HLFL212-36 HLFL212-38 HLFL212-39	2 1/4 2 3/8 2 7/16	9.8425 250	7.9528 202	5.5118 140	1.1417 29	0.7087 18	1.8898 48	0.6496 16.5	2.6260 66.7	1.0000 25.4	5/8 16	HL212-36 HL212-38 HL212-39	FL212	9.30

Refer to recommended cap screw tightening torque table for proper tightening torques.