



Standard B Type Seal



Optional Triple-lip seal
(+ Suffix - R3)

HLU Unit No.	Shaft Diameter in.	Dimensions (in./mm)										Bolt Used (in./mm)	Bearing No.	Housing No.	Weight lbs
		H	L	J	A	N	N1	H1	H2	S	B				
HLP204-12	3/4	1.3110 33.3	5.0000 127	3.7402 95	1.3780 35	0.5118 13	0.7480 19	0.5512 14	2.5590 65	0.5000 12.7	1.2795 32.5	3/8 10	HL204-12	P204	1.73
HLP205-15 HLP205-16	15/16 1	1.4370 36.5	5.5118 140	4.1338 105	1.4961 38	0.5118 13	0.7480 19	0.5906 15	2.7953 71	0.5630 14.3	1.4370 36.5	3/8 10	HL205-15 HL205-16	P205	2.37
HLP206-18 HLP206-19 HLP206-20	1 1/8 1 3/16 1 1/4	1.6890 42.9	6.2992 160	4.7638 121	1.7323 44	0.5512 14	0.7480 19	0.6693 17	3.2677 83	0.6260 15.9	1.5630 39.7	1/2 12	HL206-18 HL206-19 HL206-20	P206	3.95
HLP207-20 HLP207-22 HLP207-23	1 1/4 1 5/8 1 7/16	1.8740 47.6	6.5748 167	5.0000 127	1.8898 48	0.5906 15	0.7480 19	0.7087 18	3.6614 93	0.6890 17.5	1.7913 45.5	1/2 12	HL207-20 HL207-22 HL207-23	P207	4.50
HLP208-24	1 1/2	1.9370 49.2	7.0866 180	5.3939 137	2.1260 54	0.5906 15	0.8268 21	0.7480 19	3.8583 98	0.7480 19.0	2.0000 50.8	1/2 12	HL208-24	P208	5.35
HLP209-26 HLP209-27 HLP209-28	1 5/8 1 11/16 1 3/4	2.1260 54.0	7.4803 190	5.7480 146	2.1260 54	0.5906 15	0.8268 21	0.7874 20	4.1732 106	0.7480 19.0	2.0000 50.8	1/2 12	HL209-26 HL209-27 HL209-28	P209	5.60
HLP210-31 HLP210-32	1 15/16 2	2.2520 57.2	8.1102 206	6.2598 159	2.3622 60	0.7480 19	0.8661 22	0.8268 21	4.4882 114	0.7480 19.0	2.0945 53.2	5/8 16	HL210-31 HL210-32	P210	7.25
HLP211-32 HLP211-34 HLP211-35	2 2 1/8 2 3/16	2.5000 63.5	8.6220 219	6.7323 171	2.3622 60	0.7480 19	0.8661 22	0.9055 23	4.9606 126	0.8740 22.2	2.2520 57.2	5/8 16	HL211-32 HL211-34 HL211-35	P211	8.80
HLP212-36 HLP212-38 HLP212-39	2 1/4 2 3/8 2 7/16	2.7480 69.8	9.4882 241	7.2441 184	2.7559 70	0.7480 19	0.9842 25	0.9842 25	5.4331 138	1.0000 25.4	2.6260 66.7	5/8 16	HL212-36 HL212-38 HL212-39	P212	12.25

Refer to recommended cap screw tightening torque table for proper tightening torques.