



HLU Unit No.	Shaft Diameter in.	Dimensions (in.) (mm)									Tapped Holes 2-N	Bearing No.	Housing No.	Weight lbs
		H	L	J	A	H1	H2	F	S	B				
HLP A204-12	3/4	1.3110 33.3	2.8740 73	2.0000 50.8	1.4961 38	0.4331 11	2.5591 65	1/2 13	0.500 12.7	1.2795 32.5	3/8 - 16UNC	HL204-12	PA204	1.58
HLP A205-15 HLP A205-16	1 1/16 1	1.4370 36.5	2.9921 76	2.0000 50.8	1.4961 38	0.4724 12	2.7953 71	1/2 13	0.5630 14.3	1.4370 36.5	3/8 - 16UNC	HL205-15 HL205-16	PA205	1.95
HLP A206-18 HLP A206-19 HLP A206-20	1 1/8 1 3/16 1 1/4	1.6890 42.9	4.0157 102	3.0000 76.2	1.4961 38	0.4724 12	3.4252 87	5/8 16	0.6260 15.9	1.5630 39.7	7/16 - 14UNC	HL206-18 HL206-19 HL206-20	PA206	3.20
HLP A207-20 HLP A207-22 HLP A207-23	1 1/4 1 3/8 1 7/16	1.8740 47.6	4.2520 108	3.2480 82.5	1.8898 48	0.4724 12	3.7402 95	3/4 19	0.6890 17.5	1.7913 45.5	1/2 - 13UNC	HL207-20 HL207-22 HL207-23	PA207	4.05
HLP A208-24	1 1/2	1.9370 49.2	4.6260 117.5	3.5000 88.9	1.8898 48	0.4724 12	3.9370 100	3/4 19	0.7480 19	2.0000 50.8	1/2 - 13UNC	HL208-24	PA208	4.50
HLP A209-26 HLP A209-27 HLP A209-28	1 5/8 1 11/16 1 3/4	2.1260 54	5.0000 127	3.7520 95.3	2.0079 51	0.4724 12	4.2520 108	3/4 19	0.7480 19	2.0000 50.8	1/2 - 13UNC	HL209-26 HL209-27 HL209-28	PA209	5.40
HLP A210-31 HLP A210-32	1 15/16 2	2.2500 57.15	5.5118 140	4.0000 101.6	2.0079 51	0.5512 14	4.6260 117.5	31/32 25	0.7480 19	2.0945 53.2	5/8 - 11UNC	HL210-31 HL210-32	PA210	7.00

Refer to recommended cap screw tightening torque table for proper tightening torques.