



Standard B Type Seal



Optional Triple-lip seal
(+ Suffix - R3)

HLU Unit No.	Shaft Diameter in.	Dimensions (in./mm)														Bearing No.	Housing No.	Weight lbs	
		L	L1	L2	L3	N	N1	N2	H	H1	H2	A	A1	A2	S				B
HLT204-12	3/4	3.7008 94	2.4016 61	0.3937 10	2.0079 51	0.7480 19	1.2598 32	0.6299 16	3.5039 89	2.9921 76	2.0079 51	1.2598 32	0.5315 13.5	0.8268 21	0.500 12.7	1.2795 32.5	HL204-12	T204	1.93
HLT205-15 HLT205-16	15/16 1	3.8189 97	2.4409 62	0.3937 10	2.0079 51	0.7480 19	1.2598 32	0.6299 16	3.5039 89	2.9921 76	2.0079 51	1.2598 32	0.5315 13.5	0.9449 24	0.5630 14.3	1.4370 36.5	HL205-15 HL205-16	T205	2.20
HLT206-18 HLT206-19 HLT206-20	1 1/8 1 3/16 1 1/4	4.4488 113	2.7559 70	0.3937 10	2.2441 57	0.8661 22	1.4567 37	0.6299 16	4.0157 102	3.5039 89	2.2047 56	1.4567 37	0.5315 13.5	1.1024 28	0.6260 15.9	1.5630 39.7	HL206-18 HL206-19 HL206-20	T206	3.10
HLT207-20 HLT207-22 HLT207-23	1 1/4 1 3/8 1 7/16	5.0787 129	3.0709 78	0.5118 13	2.5197 64	0.8661 22	1.4567 37	0.6299 16	4.0157 102	3.5039 89	2.5197 64	1.4567 37	0.5315 13.5	1.1811 30	0.6890 17.5	1.7913 45.5	HL207-20 HL207-22 HL207-23	T207	4.00
HLT208-24	1 1/2	5.6693 144	3.4646 88	0.6299 16	3.2677 83	1.1417 29	1.9291 49	0.7480 19	4.4882 114	3.9764 101	3.2677 83	1.9291 49	0.6890 17.5	1.2992 33	0.7480 19	2.0000 50.8	HL208-24	T208	5.50
HLT209-26 HLT209-27 HLT209-28	1 5/8 1 11/16 1 3/4	5.6693 144	3.4252 87	0.6299 16	3.2677 83	1.1417 29	1.9291 49	0.7480 19	4.6063 117	3.9764 101	3.2677 83	1.9291 49	0.6890 17.5	1.3780 35	0.7480 19	2.0000 50.8	HL209-26 HL209-27 HL209-28	T209	5.55
HLT210-31 HLT210-32	1 15/16 2	5.8661 149	3.5433 90	0.6299 16	3.3858 86	1.1417 29	1.9291 49	0.7480 19	4.6063 117	3.9764 101	3.2677 83	1.9291 49	0.6890 17.5	1.4567 37	0.7480 19	2.0945 53.2	HL210-31 HL210-32	T210	6.24
HLT211-32 HLT211-34 HLT211-35	2 2 1/8 2 3/16	6.7323 171	4.1732 106	0.7480 19	3.7405 95	1.3780 35	2.5197 64	0.9843 25	5.7480 146	5.1181 130	4.0157 102	2.5197 64	1.0630 27	1.4961 38	0.8740 22.2	2.2520 57.2	HL211-32 HL211-34 HL211-35	T211	8.80
HLT212-36 HLT212-38 HLT212-39	2 1/4 2 3/8 2 7/16	7.6378 194	4.6850 119	0.7480 19	4.0157 102	1.3780 35	2.5197 64	1.2598 32	5.7480 146	5.1181 130	4.0157 102	2.5197 64	1.0630 27	1.6535 42	1.0000 25.4	2.6260 66.7	HL212-36 HL212-38 HL212-39	T212	11.00

Refer to recommended cap screw tightening torque table for proper tightening torques.