



K Type Seal

HLU Unit No.	Shaft Diameter		Dimensions (in./mm)							Bolt Used (in./mm)	Bearing No.	Housing No. (pair)	Weight lbs
	in.	mm	L	P	A1	N	A	B1	S				
SBMS201-08	1/2	15	3.1890	2.5000	0.1575	0.2795	0.5512	0.8661	0.2362	1/4	SB201-08	40MSZP	.50
SBMS202	5/8	17	81	63.5	4	7.1	14	22	6	M6	SB202		
SBMS202-10 SBMS203	3/4	20	3.5433	2.8150	0.1575	0.3543	0.6299	0.9843	0.2756	5/16	SB202-10 SB203		
SBMS204-12 SBMS204	7/8	25	3.7402	2.9921	0.1575	0.3543	0.6693	1.0630	0.2953	5/16	SB204-12	47MSZP	.65
SBMS205-14 SBMS205-15 SBMS205	1 1/16	30	4.4488	3.5630	0.1969	0.4331	0.6693	1.1811	0.3150	3/8	SB205-14 SB205-15 SB205		
SBMS205-16	1	35	4.8031	3.9370	0.1969	0.4331	0.7874	1.2598	0.3346	3/8	SB205-16	62MSZP	1.17
SBMS206-17 SBMS206-18 SBMS206	1 1/8	40	5.8268	4.6850	0.2756	0.5315	0.9055	1.3386	0.3543	1/2	SB206-17 SB206-18 SB206		
SBMS206-19 SBMS206-20	1 3/16	45	5.9055	4.7441	0.2756	0.5315	0.9055	1.6220	0.4016	1/2	SB206-19 SB206-20		
SBMS207-20 SBMS207-21 SBMS207-22 SBMS207	1 1/4	50	6.1811	5.0000	0.3150	0.5315	0.9843	1.7126	0.4291	1/2	SB207-20 SB207-21 SB207-22 SB207	72MSZP	1.64
SBMS207-23	1 5/16	55	6.4811	5.3150	0.3500	0.5315	0.9843	1.7126	0.4291	1/2	SB207-23		
SBMS208-24 SBMS208-25 SBMS208	1 3/8	60	6.4811	5.3150	0.3500	0.5315	0.9843	1.7126	0.4291	1/2	SB208-24 SB208-25 SB208	80MSZP	2.60
SBMS209-26 SBMS209-27 SBMS209-28 SBMS209	1 7/8	65	6.8111	5.6441	0.3850	0.5315	0.9843	1.7126	0.4291	1/2	SB209-26 SB209-27 SB209-28 SB209		
SBMS210-30 SBMS210-31 SBMS210	1 15/16	70	7.1811	5.9771	0.4150	0.5315	0.9843	1.7126	0.4291	1/2	SB210-30 SB210-31 SB210		
SBMS210-32	2	75	7.5811	6.3771	0.4450	0.5315	0.9843	1.7126	0.4291	1/2	SB210-32	90MSZP	3.85

\*201 thru 207 Outer Ring sizes - 3holes @120°

\*208 thru 210 Outer Ring sizes - 4 holes @ 90°