



HLU Bearing No.	Type	Shaft Size in.	Dimensions (in.) (mm)							Load Ratings lbs		Weight lbs
			H		D		h	C	B	Dynamic Cr	Static Cor	
			Bore Nominal	Bore Tolerance	Outer Diameter	+ 0 to minus Outer Tolerance	Relube Hole Location	Outer Ring	Inner Ring			
GW208PPB5	2	1 1/8	1.1799 29.97	± .005 ± .127	3.1496 80	.0005 .013	0.2638 6.70	0.8268 21	1.4380 36.525	8093	4456	1.38
GW208PPB8	2	1 1/8	1.1799 29.97	± .005 ± .127	3.1496 80	.0005 .013	0.2650 6.73	1.1880 30.175	1.4380 36.525	8093	4456	1.47
GW208PP17	3	1 1/8	1.1799 29.97	± .005 ± .127	3.3755 85.738	.0005 .013	0.2681 6.81	1.1880 30.175	1.4380 36.525	8093	4456	1.95
GW209PPB5	2	1 1/4	1.2992 33	± .005 ± .127	3.3465 85	.0006 .015	0.2480 6.30	1.1880 30.175	1.4380 36.525	8093	4602	1.66
GW209PPB8	2	1 1/4	1.2992 33	± .005 ± .127	3.3465 85	.0006 .015	0.2539 6.45	0.8661 22	1.4380 36.525	8093	4602	1.58
GW210PP4	4	1 1/8	1.1799 29.97	± .005 ± .127	3.5433 90	.0006 .015	0.2390 6.07	1.1880 30.175	1.1880 30.175	8835	5212	2.00
GW210PPB4	1	1 1/8	1.1799 29.97	± .005 ± .127	3.5433 90	.0006 .015	0.2390 6.07	1.1880 30.175	1.1880 30.175	8835	5212	1.87
GW211PP3	4	1 1/2	1.5311 38.89	± .005 ± .127	3.9370 100	.0006 .015	0.2638 6.70	1.3120 33.325	1.3120 33.325	9756	6571	2.44
GW211PPB3	1	1 1/2	1.5311 38.89	± .005 ± .127	3.9370 100	.0006 .015	0.2638 6.70	1.3120 33.325	1.3120 33.325	9756	6571	2.33
GW211PP17	3	1 1/2	1.5311 38.89	± .005 ± .127	3.9370 100	.0006 .015	0.2638 6.70	1.3120 33.325	1.7500 44.45	9756	6571	2.98
GW211PPB23	2	1 1/2	1.5311 38.89	± .005 ± .127	3.9370 100	.0006 .015	0.2638 6.70	1.3120 33.325	1.7500 44.45	9756	6571	2.75
DC212TTR	3	1 3/4	1.7913 45.50	± .005 ± .130	4.3307 110	.0006 .015	0.2992 7.60	1.5059 38.25	2.0000 50.8	10723	7440	3.77
GW216PP2	3	2 1/4	2.2913 58.2	± .0098 ± .250	5.5118 140	.0008 .020	0.3504 8.90	1.1811 30	2.5000 63.50	16082	12213	7.28
GW216PPB2	2	2 1/4	2.2913 58.2	± .0098 ± .250	5.5118 140	.0008 .020	0.3504 8.90	1.1811 30	2.5000 63.50	16082	12213	7.05

* For outer ring sizes through 212.