



HLU Unit No.	Type		Shaft Size	Dimensions (in.)									Load Rating lbs		Weight lbs
				A	B	C	E	F	L	N	N1	N2	Dymanic Cr	Static Cor	
208 SERIES	Front	Side	in.	in.	in.	in.	in.	in.	in.	in.	in.	in.			
ST208-1N*	3	B	1 SQ.	1.378	1.503	4.687	0.276	3.570	4.764	-	0.531	0.531	7328	4450	3.05
ST208-1 42LTB	3	B	1 SQ.	1.378	1.654	4.687	0.276	3.570	4.764	-	0.531	0.531	7328	4450	3.20
ST208-1 1/8	3	B	1 1/8 SQ.	1.378	1.503	4.687	0.276	3.570	4.764	-	0.531	0.531	7328	4450	2.90
ST208-1 1/8N*	3	B	1 1/8 SQ.	1.378	1.503	4.687	0.276	3.570	4.764	-	0.531	0.531	7328	4450	2.90
209 SERIES															
ST209-1 1/8	4	B	1 1/8 SQ.	1.654	1.685	5.000	0.276	3.859	5.000	-	0.531	0.687	7350	4608	3.80
ST209-1 1/4	4	B	1 1/4 SQ.	1.654	1.685	5.000	0.276	3.859	5.000	-	0.531	0.687	7350	4608	3.75
ST491B	2	A	1 1/2 RD.	1.654	1.685	5.000	0.276	3.859	5.000	-	0.531	0.687	7350	4608	3.70
ST491A	1	A	1 3/4 RD.	1.654	1.685	5.000	0.276	3.859	5.000	0.531	-	-	7350	4608	3.35
ST209-1 1/2 JD KIT**	5	D	1 1/2 RD.	1.945	1.438	4.748	0.331	3.680	5.866	-	0.528	0.528	8092	4602	4.20
ST209-1 3/4 JD KIT**	5	D	1 3/4 RD.	1.945	1.438	4.748	0.331	3.680	5.866	-	0.528	0.528	8092	4602	4.20
211 SERIES															
ST211-1 1/2	4	B	1 1/2 SQ	1.827	2.000	5.500	0.354	4.469	5.500	-	0.531	0.594	9756	6564	5.65
ST211-1 3/4	1	A	1 3/4 RD.	1.827	2.189	5.500	0.354	4.469	5.500	0.531	-	-	9756	6564	5.85
ST211-1 15/16	1	C	1 15/16 RD.	1.827	2.752	5.500	0.354	4.469	5.500	0.531	-	-	9756	6564	5.50
ST211-2 3/16	1	A	2 3/16 RD.	1.750	2.189	5.500	0.354	4.469	5.500	0.531	-	-	9756	6564	5.00
ST211-2 3/16 JD KIT**	5	D	2 3/16 RD.	2.220	1.563	5.433	0.411	4.375	6.575	-	0.528	0.528	9756	6510	6.10

* N suffix indicates non-regreasable.

** Replacement bearings, stamping, gaskets and bolts available for ST209-1 1/2 JD KIT, ST209 1 1/4 JD Kit and ST211 2 3/16 JD KIT.